

CONSTRUCTION HOISTS

POTAIN®

SC 220 65A M A

Cage size : 3.2 m x 1.5 m x 2.3 m
Max payload capacity : 2200 kg
Lifting speed(Normal) : 43 m/min

TECHNICAL SPECIFICATIONS

Cage sizes(LxWxH)	3.2 m x 1.5 m x 2.3 m
Max. payload capacity	2200 kg
Cage door opening sizes (W x H)	1.5 m x 2.0 m
C Door sizes (W x H)	1.5 m x 2.0 m
Max. interval of mast ties	12 m
Maximum mast height	200 m
Mast section sizes	650mm x 650mm x 1508mm
Rack module	5 mm
Safety device type	SAJ50-2.0

LIFTING SPEEDS

Lifting Speed (Normal)	43 m/min
Lifting speed(Instl./Dismtl./Inspt.)	9 m/min

GROUND STATION DIMENSIONS

Ground Station (LxW)	3.85m x 2.8m
----------------------	--------------

POWER SUPPLY

Motor control	Frequency control
Number of motors	2 x 20 kW
Power supply range	380~500V, 50Hz/60Hz, 3 Phase
RCD protection	30 mA
Rated current	58 A
Fuse ratings	83 A

OPTIONAL CONFIGURATION

- 1) For other demands or specifications, please consult Potain.
- 2) Power supply: Bus Bar or Cable trolley

